

Pay-N-Save Product Catalog

Oct 16, 2026 · @christian

Notes for the web designer

This catalog lists every product Pay-N-Save wants on the website, grouped by brand and category. Each row has the product name, manufacturer part or model number, a short description written for our site, key specs, and a link to a product page with a photo.

- **Photos:** use the image on the linked page, or the manufacturer's own site. For high-resolution images, ask Pay-N-Save to request them from the brand's dealer rep.
- **Descriptions** are original copy for our site. Please don't paste manufacturer text.
- **Pricing** is not included. Show "Call for pricing" or a quote button.
- Part numbers are the manufacturer's. Keep them visible, since contractors search by them.

Polylok septic products

Polylok makes HDPE risers, seals, filters and distribution boxes for septic tanks. Risers stack and screw together to bring tank access up to grade; seal joints with butyl sealant tape, since new risers ship without a factory gasket.

Septic tank risers

Product	Part #	Description	Key specs	Photo / product page
Polylok 24" x 12" Riser	3008-R12	Tall stackable riser to bring 24" tank access to grade with fewer joints.	24" dia. x 12" tall, HDPE, green, screws included	View
Polylok 20" x 12" Riser	3009-R12	Tall stackable riser for 20" tank openings and Polylok 6- and 8-hole D-boxes.	20" dia. x 12" tall, HDPE, screws included	View

Product	Part #	Description	Key specs	Photo / product page
Polylok 24" x 6" Riser	3008	Mid-height section for building a 24" riser stack to the exact depth needed.	24" dia. x 6" tall, HDPE	View
Polylok 20" x 6" Riser	3009	Mid-height section for 20" riser stacks and D-boxes.	20" dia. x 6" tall, HDPE	View
Polylok 24" x 2" Grade Riser	3008-GR2	Low-profile ring for fine-tuning a 24" riser to finished grade.	24" dia. x 2" tall, HDPE	View
Polylok 20" x 2" Grade Riser	3009-GR2	Low-profile ring for fine-tuning a 20" riser or D-box to grade.	20" dia. x 2" tall, HDPE	View

Seals, adapters, filters and D-boxes

Product	Part #	Description	Key specs	Photo / product page
Polylok Uni-Seal grommet, 2"	3007-GM2	Push-in grommet that seals a pipe through a riser or tank wall with no tools or sealant.	Fits 2" SCH 40, SDR 35 or steel pipe; PVC/rubber	View
Polylok Uni-Seal grommet, 1"	3007-GM1	Same push-in grommet for 1" pump discharge lines.	Fits 1" pipe	View
Polylok Uni-Seal grommet, 3/4"	3007-GM.75	Same push-in grommet for 3/4" lines and conduit.	Fits 3/4" pipe	View

Product	Part #	Description	Key specs	Photo / product page
Polylok Extend & Lok, 4"	30130-TL	Extends a short tank outlet pipe so a filter or tee can be centred under the riser. No glue needed.	Fits 4" SCH 40 pipe, PVC	View
Polylok PL-122 Effluent Filter	3014-PA (PL-122)	Outlet filter that keeps solids in the tank and out of the field. An automatic shut-off ball stops flow while the filter is pulled for cleaning.	122 linear ft of 1/16" slots, up to 3,000 GPD, fits 4" SCH 40, NSF/ANSI 46	View
Polylok 20" 8-Hole Distribution Box	3017-20	Large D-box that splits flow evenly to field laterals. You choose inlet and outlet positions; accepts 20" risers.	20" dia., 8 knock-outs, accepts 2", 3", 4" and 6" pipe, flat cover, max 4 ft burial	View

Spec sheets: [Polylok drainage catalog \(PDF\)](#) · [PL-122 sheet \(PDF\)](#) · Manufacturer site: polylok.com

SJE Rhombus control panels, alarms and floats

SJE Rhombus makes the panels, alarms and float switches that run and monitor septic and effluent pumps. All products below are UL Listed and CSA Certified.

Pump control panels

Product	Model / part #	Description	Key specs	Photo / product page
SJE IFS Simplex Panel, 20 A	IFN21W124X6A8AC10E	Installer Friendly Series panel for one pump, with colour LCD programming. Switches between demand dose and timed dose in the field.	1 pump, 120/208/240 V single phase, 15–20 A, NEMA 4X 12" x 10" x 6", float or C-Level sensor	View
SJE IFS Simplex Panel, 15 A	IFN21W114X6A8AC10E	Same Installer Friendly simplex panel for smaller pumps.	1 pump, 120/208/240 V single phase, 7–15 A, NEMA 4X	View
SJE IFS Duplex Panel, 20 A	IFN41W124X6A8AC10E	Installer Friendly panel that alternates two pumps, with backup if one fails. LCD programming, demand or timed dose.	2 pumps, 120/208/240 V single phase, 15–20 A, NEMA 4X	View
SJE Model 115 Simplex Panel	1151W200H17A	Simple, reliable panel: a pump switch runs the pump and a separate float triggers the alarm beacon and horn.	1 pump, 120/240 V single phase, red alarm beacon, horn silence	View

Alarms

Product	Model / part #	Description	Key specs	Photo / product page
SJE Tank Alert AB	1011421 (TAAB-01H)	Indoor high-level alarm with battery backup, for sumps, pump chambers and holding tanks. Comes with float.	120 V, horn + red light, auto reset, low-battery chirp, 6 ft cord, NEMA 1	View
SJE Tank Alert XT with float	1009923 (TAXT-01H)	Indoor/outdoor high-level alarm with red beacon and horn. Ready to install with 15 ft float and clamp.	120 V, 85 dB horn, Type 3R/4X, auto reset, test/silence switch	View
SJE Double Holding Tank Alarm	SWR P/OUT TNK ALARM	Two-level alarm for pump-out holding tanks: warns when the tank is nearly full, then again at full.	Two alarm points, indoor/outdoor	Photo from SJE rep

Floats and accessories

Product	Model / part #	Description	Key specs	Photo / product page
SJE SignalMaster SPDT Control Switch	1006101 (30SGMSPDTWE)	Narrow-angle float that signals control panels and alarms. Wires as high level (NO) or low level (NC).	30 ft cord, 5 A, 125/250 VAC, externally weighted, green cap	View

Product	Model / part #	Description	Key specs	Photo / product page
SJE PumpMaster Pump Switch	1002727 (20PMD1WP)	Wide-angle piggyback float that turns a pump on and off directly. Pump-down (emptying) model.	20 ft cord with plug, 120 V, up to 1/2 HP, 7-36" pumping range	View
SJE 4-Float Bracket	1009432	Stainless bracket that holds up to four floats and stores extra cord neatly in the tank.	300 series stainless, wall mount device and strain reliefs included	View

Spec sheets: [Tank Alert XT \(PDF\)](#) · [SignalMaster SPDT \(PDF\)](#) · [PumpMaster \(PDF\)](#) ·
 Manufacturer site: sjerhombus.com

Goulds pumps

Pay-N-Save is an authorized Goulds dealer. The WE series (model 3885) is the workhorse cast-iron effluent pump for septic dosing and pump chambers; the WS series (model 3886) handles raw sewage with 2" solids; the PE series is a compact effluent pump for mound and low-pressure systems. All listed models are manual (no float), 20 ft cord, UL and CSA listed.

Effluent pumps

Product	Model	Description	Key specs	Photo / product page
Goulds WE 3/4 HP Effluent Pump	WE0712H	Continuous-duty cast-iron effluent pump for larger dosing systems, schools and commercial sites. Can run dry without damage.	3/4 HP, 230 V, 1 ph, 10 A, 2" NPT, 3/4" solids	View
Goulds WE 1/2 HP Effluent Pump, high head	WE0511HH	High-head version of the 1/2 HP WE, for systems that pump uphill or a long distance.	1/2 HP, 115 V, 1 ph, 14.5 A, 2" NPT, 3/4" solids	View
Goulds WE 1/2 HP Effluent Pump	WE0511H	All-round residential effluent pump for septic pump chambers.	1/2 HP, 115 V, 1 ph, 14.5 A, 2" NPT, 3/4" solids, 3450 RPM	View
Goulds WE 1/3 HP Effluent Pump, medium head	WE0311M	Lower-horsepower WE for moderate lift dosing systems.	1/3 HP, 115 V, 1 ph, 10.7 A, 2" NPT, 1750 RPM	View
Goulds WE 1/3 HP Effluent Pump, low head	WE0311L	Low-head WE that moves high volume over short lifts, such as gravity-fed fields.	1/3 HP, 115 V, 1 ph, 10.7 A, 2" NPT, 1750 RPM	View
Goulds PE 1/3 HP Effluent Pump	PE31M	Compact, lightweight effluent pump for mound systems, low-pressure pipe and basement drainage.	1/3 HP, 115 V, 12 A, 1-1/2" NPT, up to 53 GPM / 25 ft, 1/2" solids	View

Sewage pumps

Product	Model	Description	Key specs	Photo / product page
Goulds WS 1/2 HP Sewage Pump, 115 V	WS0511B	Cast-iron sewage pump that passes 2" solids, for homes, lift stations and dewatering.	1/2 HP, 115 V, 14.5 A, 2" NPT, up to 185 GPM / 38 ft, 2" solids	View
Goulds WS 1/2 HP Sewage Pump, 230 V	WS0512B	Same WS sewage pump wired for 230 V service.	1/2 HP, 230 V, 1 ph, 2" NPT, 2" solids	View

Spec sheets: [PE series brochure \(PDF\)](#) · Manufacturer site: xylem.com/goulds

Myers pumps

Myers (Pentair) cast-iron effluent pumps are a strong alternative for septic dosing, with oil-filled PSC motors and enclosed impellers that resist jamming.

Product	Model	Description	Key specs	Photo / product page
Myers ME45 1/2 HP Effluent Pump	ME45MC-11	Residential effluent and sump pump for septic tanks and dosing systems. Quick-connect cords make service easy.	1/2 HP, 115 V, 8.6 A, 2" NPT, 3/4" solids, up to 87 GPM / 44 ft, 20 ft cord, manual	View
Myers ME 1/2 HP High-Head Effluent Pump	ME50S-11	Built for mound and trench pressure-distribution systems that need more head. Enclosed two-vane impeller, single seal.	1/2 HP, 115 V, 2" NPT, 3/4" solids, up to 120 GPM / 95 ft, 20 ft cord, manual	View

Manufacturer site: [Myers / Pentair](#)

PVC pipe, fittings and couplers

Pay-N-Save stocks CSA-approved Schedule 40 PVC pressure pipe and fittings from 3/4" to 4", plus 4" sewer pipe and flexible couplers. Pipe is solvent-weld and rated for buried or above-ground use with cold water. Schedule 40 meets CSA B137.3 and ASTM D1785 ([IPEX spec](#)).

Schedule 40 PVC pressure pipe and fittings

Size	Typical uses	Working pressure at 73°F
3/4"	Irrigation laterals, pump discharge	480 psi
1"	Irrigation laterals and mains, effluent discharge	450 psi
1-1/4"	Pump discharge, irrigation mains	370 psi
1-1/2"	Effluent force mains, irrigation mains	330 psi
2"	Effluent and sewage force mains, irrigation mains	280 psi
3"	Mains, drainage	260 psi
4"	Mains, septic tank inlet and outlet	220 psi

Fittings in every size: couplings, 90° and 45° elbows, tees, male and female adapters, caps and reducers. Photo: one generic shot of white Schedule 40 pipe and a fitting group works for the whole line.

Sewer pipe and couplers

Product	Part #	Description	Key specs	Photo / product page
IPEX 4" PVC Sewer Pipe, solid	004043	Solid-wall BDS (building drain and sewer) pipe for building sewers and septic tank inlet and outlet lines. Solvent-weld joints.	4" x 10 ft, CSA B182.1, gravity (non-pressure), max 140°F	View
IPEX 4" PVC Sewer Pipe, perforated	003445	Perforated BDS pipe that spreads effluent across septic fields and drains foundations and landscapes.	4" x 10 ft, perforated, CSA B182.1, solvent weld, gravity (non-pressure)	View
Fernco 4" Flexible Coupling	1056-44	Rubber coupler that joins pipes of the same or different materials, such as PVC to cast iron. No glue needed.	4", flexible PVC, two stainless clamps, -30 to 140°F, CSA B602	View

Hunter irrigation

Pay-N-Save is an authorized Hunter dealer. Rotors cover large turf areas; Pro-Spray bodies with Pro Adjustable nozzles cover small lawns and beds; PGV valves open and close each zone on the controller's signal.

Rotors

Product	Model	Description	Key specs	Photo / product page
Hunter I-20 Rotor, 4"	I-20-04	Durable commercial-grade rotor for mid-size turf, with automatic arc return and a drain check valve built in.	3/4" inlet, 4" pop-up, 50–360° arc, approx. 17–46 ft radius, check valve	View
Hunter I-25 Rotor, 4"	I-25-04	Large-turf rotor for parks, schools and sports fields.	1" inlet, 4" pop-up, 40–71 ft radius, 3.8–31.5 GPM, 40–100 PSI, 5-yr warranty	View
Hunter I-40 Rotor, 4", stainless riser	I-40-04-SS	Heavy-duty rotor with stainless steel riser for high-traffic or vandal-prone sites. Six nozzles included.	1" inlet, 4" pop-up, 44–69 ft radius, 7.6–29.5 GPM, 50–360° arc, check valve	View
Hunter PGP-ADJ Rotor	PGP-ADJ	Proven residential rotor for medium lawns. Comes with a rack of 12 nozzles.	3/4" inlet, 4" pop-up, 40–360° arc, approx. 21–52 ft radius	View
Hunter PGJ Rotor, 4"	PGJ-04	Compact rotor that brings rotor efficiency to small spaces usually watered with sprays.	1/2" inlet, 4" pop-up, 40–360° arc, approx. 15–34 ft radius, 2.0 nozzle installed	View

Spray bodies and nozzles

Product	Model	Description	Key specs	Photo / product page
Hunter Pro-Spray 6" with check valve	PROS-06-CV	Tall pop-up spray body for shrub beds and longer grass; check valve stops low-head drainage on slopes.	1/2" female inlet, 6" pop-up, factory check valve	View
Hunter Pro-Spray 4" with check valve	PROS-04-CV	Standard lawn spray body with check valve.	1/2" female inlet, 4" pop-up, factory check valve	View
Hunter Pro-Spray 2"	PROS-02	Low-profile spray body for short turf and edges.	1/2" female inlet, 2" pop-up	View
Hunter Pro Adjustable Nozzles	4A, 8A, 10A, 12A, 15A, 17A	Colour-coded spray nozzles with arc adjustable from 0° to 360°. Large droplets resist wind. Fit Pro-Spray and other female-thread bodies.	Radius 4, 8, 10, 12, 15, 17 ft; 30 PSI recommended; 2-yr warranty	View

Valves

Product	Model	Description	Key specs	Photo / product page
Hunter PGV 1" Valve, FPT	PGV-100-G	Reliable residential zone valve with internal/external manual bleed.	1" female thread, no flow control, 0.2-40 GPM, 24 VAC	View

Product	Model	Description	Key specs	Photo / product page
Hunter PGV 1" Valve, slip	PGV-100-G-S	Same valve with glue-on slip ends.	1" slip x slip, no flow control, 0.2–40 GPM	View
Hunter PGV 1" Valve with flow control, FPT	PGV-101-G	Adds flow control for fine-tuning each zone. Residential and light commercial.	1" female thread, flow control, 0.2–40 GPM	View
Hunter PGV 1" Valve with flow control, slip	PGV-101-G-S	Flow-control valve with slip ends.	1" slip x slip, flow control, 0.2–40 GPM	View

Spec sheets: [PGV 1" cut sheet \(PDF\)](#) · Manufacturer site: hunterindustries.com

Irritrol valves

Irritrol valves are built for tough water: the 700 series has a self-cleaning screen and the 2500 handles wells and dirty water.

Product	Model	Description	Key specs	Photo / product page
Irritrol 700 UltraFlow Valve, 3/4"	700B-.75	Straight-through valve with very low pressure loss and slow closing to reduce water hammer.	3/4" FPT, flow control, 0.1–180 GPM (series), glass-reinforced nylon, 24 VAC	View
Irritrol 700 UltraFlow Valve, 1"	700-1	Same UltraFlow design in 1", with stainless 150-mesh self-cleaning screen.	1" FPT, flow control, 24 VAC	View

Product	Model	Description	Key specs	Photo / product page
Irritrol 2500 Valve, 1" slip	2500SF	Dirty-water valve with a floating metering system, ideal for well-fed systems.	1" slip, flow control, 0.25–30 GPM, PVC and stainless, 5-yr warranty	View
Irritrol 100 Series Valve, 3"	100P3	Large commercial globe/angle valve for main lines and big zones.	3", flow control, 20–220 PSI	View

Pay-N-Save confirms the 100P3 stays in the catalog.

Spec sheet: [2500 series \(PDF\)](#) · Manufacturer site: irritrol.com

Toro valves

Toro P-220 valves are heavy-duty commercial valves for main lines and large zones at parks, schools and sports fields.

Product	Model	Description	Key specs	Photo / product page
Toro P-220 Electric Valve, 1-1/2"	P220-26-06	Glass-filled nylon valve rated to 220 PSI, with flow control and internal/external manual bleed. Installs as globe or angle.	1-1/2" FNPT, 24 VAC, built-in Schrader port for pressure checks, EZReg regulator ready	View
Toro P-220 Electric Valve, 2"	P220-26-08	Same P-220 build in 2", with a filter screen to keep debris out of the valve.	2" FNPT, 24 VAC, up to 220 PSI, flow control, globe/angle	View

Pressure-regulating versions (EZReg) are P220-27-06 and P220-27-08. Spec sheet: [P-220 series \(PDF\)](#) · Manufacturer site: toro.com